



NOTE: ALL UNSPECIFIED DIMENSIONS ARE HAVING TOLERANCE OF ± 0.1 mm.

SPECIFICATIONS

MODEL	POWER IN WATTS/HP	SPEED IN RPM	VOLTAGE IN VDC	CURR. IN AMPS	RATIO	OUTPUT SPEED IN RPM	TORQUE IN KG-CM	INSL. CLASS	DUTY CYCLE	PROTEC-TION	ENCL.	WEIGHT (KG)	DYN AFLUX			PMD C MOTOR.									
M1INA	40 / 0.05	1500	180	0.4	5	300	4	B	S1	IP44	TENV	5.0	TITLE 75 dia IN LINE FLANGE			MMC ELECTRIC COMPANY PVT.LTD. BELGAUM.									
M1INB	40 / 0.05	1500	180	0.4	10	150	8	B	S1	IP44	TENV		REVISION NO.		REVISION DATE.										
M1INC	40 / 0.05	1500	180	0.4	25	60	20	B	S1	IP44	TENV		00		05/06/2009										
M2INA	75 / 0.10	1500	180	0.5	5	300	8	B	S1	IP44	TENV		DRAWN BY.			APPROVED BY.									
M2INB	75 / 0.10	1500	180	0.5	10	150	16	B	S1	IP44	TENV		MANOHAR			R.S.KUNDGOLKAR.									
M2INC	75 / 0.10	1500	180	0.5	25	60	40	B	S1	IP44	TENV					SHEET 1 OF 1 MATERIAL									
Mounting : Foot Cum Flange												SCALE.		N.T.S.				-----							
ALL DIMENSIONS ARE IN MM.												REV.NO		DATE		DESCRIPTION		DRN.BY		APD.BY		DRG.NO		MI-75/124-M	